

Assembly Instructions for EJOT® Solar Fastening Systems JA3 & JZ3





EJOT Solar Fastening Systems JA3 & JZ3 are for installations on exposed fastener metal roofs (trapezoidal or corrugated) or roofs with corrugated fiber cement panels only!

The Fastening Systems are always fastened into the load bearing roof substructure.

The roof substructure could be made of steel (JZ3) or timber (JA3).

- ❑ For the diameter of the pre-drill hole observe the table below (metric drills have to be used!)
- ❑ Select the length of the drill bit as well as the depth of the pilot hole according to the length of the Fastening System
- ❑ The depth of the pilot hole should be 3/8" (10 mm) deeper than the embedment of the Fastening Systems
- ❑ Assure the pre-drill hole is perpendicular to the roof surface
- ❑ Remove from the surface any chips from drilling
- ❑ When using an EJOT ORKANM Storm Washer apply it onto the crown of the trapezoidal roof profile before screwing the Fastening System in
- ❑ Install the Fastening System using an electrical screwdriver at max. 100 rpm equipped with a suitable bit (Observe the table below to select the appropriate drive bit; metric bits have to be used!)
- ❑ The compression of the sealing washer or the sealing element FZD should be 25% (Visual check: rubber is squeezed almost flush to steel washer diameter)

Not complying with these instructions leads to invalidation of warranty! For further information download EJOT Solar Fastening Systems JA3 & JZ3 Installation Manual from www.ejot-usa.com or contact us directly.



Compression of the washer or other sealing element

- 1. Too loose**
Sealing element is not seated solidly on the surface
The initial tension is too low
- 2. Correct**
The sealing element is seated solidly
- 3. Too tight**
Fastened too tight
Sealing element might be damaged



The extension of warranty is based on the usage of correctly dimensioned and exclusively original EJOT components, as well as a proper installation as shown in the installation manual. The usage of operating materials (ec. silicon) has to be omitted.

EJOT Solar Fastening	Denomination	Substructure	Pre-drilling Ø	Drive at setscrew	Screw length/ intrusion
	JZ3-SB-8.0xL/LG-E16 + Storm Washer	Steel US steel gauge 16 ≤ US steel gage 6 (1.5 mm < 5.0 mm)	6.8 mm	A/F 5mm (internal hexagon with width across flats 5 mm)	Screw length: thickness of sandwich panel or height of trapezoidal profile + 0.787" (20 mm)
		US steel gauge 5 ≤ 9/32" (5.0 mm < 7.5 mm)	7.0 mm		
	JZ3-SB-8.0xL/LG-FZD	19/64" ≤ 25/64" (7.5 mm < 10 mm)	7.2 mm		
		≥ 13/32" (≥ 10.0 mm)	7.4 mm		
	JA3-SB-8.0xL/LGE16 + Storm Washer	Wood	5.5 mm		Embedment in wood: 1.260" - 3.780" (32 - 96 mm)

Limited Warranty for function of the EJOT® Solar Fastening Systems JA3 & JZ3

Limited Warranty:

The EJOT Group warrants and represents to the purchaser of EJOT Solar Fastening Systems that the products shall be free from defects in material and workmanship under normal and expected use and service for the express period of warranty set forth below.

Period of Warranty:

The period of warranty is 10 years and starts on the date of purchase by the initial purchaser.

Warranty terms:

This warranty is valid only within the express period of warranty. This warranty is limited to either the repair or replacement, at the EJOT Group's sole option, of any defective product. Repair or replacement will only be carried out for the benefit of the direct purchaser of EJOT products. The purchaser shall pay all shipping charges for return of a defective product. For a product returned within 1 year of the date of initial purchase, the EJOT Group shall pay all shipping charges for shipment of the repaired or replacement product, as the case may be, to the purchaser. For a product returned more than 1 year after the initial date of purchase, the purchaser shall pay all shipping charges for shipment of the repaired or replacement product, as the case may be, to the purchaser. A warranty claim can only be confirmed upon presentation of the defective product, the contract receipt and lot number.

Warranty exclusions:

This limited warranty does not apply if the product is improperly installed or assembled, misapplied, abused, altered or otherwise misused in any way, including, without limitation:

- Inappropriate and improper use
- Faulty or negligent treatment
- Failure of installation and assembly instructions
- Changes and self-repairs
- Improper use with chemical and physical resulting effects on the material surface (e.g. damage caused by sharp objects)
- Use of third-party parts (i.e., non-EJOT parts or non-EJOT specified vendor parts)

Note that professional installation by an expert is required. The following assembly instruction indicates how the installation of the EJOT Solar Fastening is properly carried out and which points must be followed. Nevertheless, the following points must be guaranteed by the installer:

- It must be ensured that the use of EJOT solutions and other products are suitable for the application and installation environment.
- The project must be confirmed according to structural analysis.
- The installer must have sufficient knowledge and ability to carry out the assembly.
- Only EJOT products or EJOT specified vendor parts are allowed to be used. The use of third-party parts will void the warranty.

DISCLAIMER:

Except for the warranties set forth above, the EJOT Group makes no representations or warranties of any kind whatsoever, express or implied, including, without limitation, warranties of merchantability, noninfringement and fitness for a particular purpose, concerning any product. All other guarantees, warranties, conditions and representations, either express or implied, whether arising out of any statute, law, commercial usage or otherwise, are hereby excluded.

While the EJOT Group and its representatives may, from time to time, offer recommendations and advice with respect to use of the products, it is understood that any such recommendations and advice are not warranties by the EJOT Group and the purchaser will act upon any such recommendations and advice at the purchaser's sole risk.

Purchaser's Remedies:

The purchaser's exclusive and sole remedy on account of or in respect to the furnishing of a defective product shall be to secure repair or replacement thereof as described above. The EJOT Group shall not in any event be liable for the cost of any labor expended on any such product or for any special, direct, indirect, consequential or incidental damages (including, without limitation, loss of business or lost profits) to anyone by reason of a defective product. The EJOT Group shall not in any event be liable for damages of the purchaser relating to patent or trademark infringements.

Warranty Claim Process:

For complaints, please contact your supplier directly to present the defective product, the contract receipt and lot number.

Validity of general terms and conditions:

Overall the standard business conditions of the EJOT Group are valid. These terms and conditions can be reviewed on our website www.ejot.com under EJOT Group in the footer.