

Solis-(125-255)K-EHV-5G-US

Solis Three Phase US Inverters



>> Models:

- | | |
|---------------------------|---------------------------|
| Solis-125K-EHV-5G-US-PLUS | Solis-255K-EHV-5G-US |
| Solis-185K-EHV-5G-US | Solis-255K-EHV-5G-US-PLUS |
| Solis-185K-EHV-5G-US-PLUS | |



Efficient

- 9/12/14 MPPTs, max. efficiency 99.0% (CEC efficiency 98.3%)
- > 1.5 DC/AC ratio
- High power tracking density 75MPPT/MW
- Compatible with 500W+ bifacial modules

Safe

- Type 4X, C5 Anti-Corrosion Level
- UL 1741 SA and SB
- Integrated nighttime PID recovery for optimal module performance
- Fuse free design, safe and maintenance free
- AFCI protection, proactively reduces fire risk
- High quality components from globally recognized suppliers

Smart

- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation*

Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector
- Support aluminium wire to reduce cost
- Reserve DC energy storage access

DATASHEET**Solis-(125-255)K-EHV-5G-US**

Models	125K-PLUS	185K	185K-PLUS	255K	255K-PLUS
Input DC					
Max. input voltage			1500 V		
Rated voltage		950 V		1080 V	
Start-up voltage			500 V		
MPPT voltage range			480-1500 V		
Max. input current	9*30 A	14*26 A	12*30 A	14*26 A	12*30 A
Max. short circuit current	9*50 A	14*40 A	12*50 A	14*40 A	12*50 A
MPPT number/Max. input strings number	9/18	14/28	12/24	14/28	12/24
Output AC					
Rated output power	125 kW		185 kW		255 kW
Max. apparent output power	137.5 kVA		185 kVA		255 kVA
Max. output power	137.5 kW		185 kW		255 kW
Rated grid voltage		3Φ/PE, 600 V			3Φ/PE, 800 V
Rated grid frequency			60 Hz		
Max. output current	132.3 A		178.0 A		184.0 A
Power factor			>0.99 (0.8 leading - 0.8 lagging)		
THDi			<3%		
Efficiency					
Max. efficiency	98.6%		98.7%		99.0%
CEC efficiency			98.3%		
Protection					
DC reverse-polarity protection			Yes		
Surge protection			DC Type II / AC Type II		
Ground fault monitoring			Yes		
Anti-islanding protection			Yes		
Strings monitoring			Yes		
Integrated AFCI (DC arc-fault circuit protection)			Yes		
I/V Curve scanning			Yes		
Integrated PID recovery			Yes		
General Data					
Dimensions (W*H*D)			46.1*30.3*15.1 in (1170*770*384 mm)		
Weight	240 lbs (109 kgs)		249.0 lbs (113 kgs)		
Topology			Transformerless		
Self-consumption (night)			<2 W		
Relative humidity			0-100%		
Ambient operating temperature range			-22°F to 140°F (-30°C ~ +60°C)		
Storage environment			-40°F to 176°F (-40°C to 80°C)		
Ingress protection			TYPE 4X		
Cooling concept			Intelligent redundant fan-cooling		
Max. operation altitude			13,120 ft (4000 m)		
Compliance	UL 1741SB, UL 1741SA, UL 1998, UL1699B, IEEE 1547-2018, FCC Part 15 (Class A & B), CAN/CSA C22.2 107.1-1, California Rule 21				
Features					
DC connection			MC4 connector		
AC connection			OT terminal (750 MCM)		
Display			LCD		
Communication			RS485, Optional: PLC		