

NEW
30K

SOLARATOR SERIES

Operates Seamlessly with Generators: Experience Uninterrupted Power, Even in Areas with Grid Instability

S6-EH3P30K03-LV-YD-H-US

Three Phase | High Voltage



- High input current (40A) supports larger modules, improving power density and eliminating clipping
- More seamless system operation and resiliency with fast and automated battery charge/discharging
- Compatible with 100-280Ah battery modules, driving down system costs and enhancing flexibility, wide range for generator power as well
- Extremely flexible configurations, storage use mode features and battery options
- Supports 200% oversizing for maximizing PV utilization
- Easily add inverter capacity, PV or batteries to scale up as you grow thanks to dual input flexibility
- Stability during and after outages with 160% overload capacity

USA

t: +1 866 438 8408

w: solisinverters.com/us

e: ussales@solisinverters.com

usservice@solisinverters.com



DATASHEET

S6-EH3P30K03-LV-YD-H-US

Models	30K
Input DC (PV side)	
Max. usable PV input power	60 kW
Max. input voltage	1000 V
Rated voltage	600 V
Start-up voltage	180 V
MPPT voltage range	150 - 850 V
Max. input current	40 A / 40 A / 40 A
Max. short circuit current	65 A / 65 A / 65 A
MPPT number / Max. input strings number	3 / 6
Max input power per MPPT	25 kW (600 V × 40 A)
Battery	
Battery type	Li-ion
Battery voltage range	150 - 800 V
Max. charge / discharge power	33 kW
Max. charge / discharge current	70 A × 2 ^①
Number of battery ports	2
Max. charge / discharge power of each input	33 kW
Communication	CAN / RS485
Output AC (Grid side)	
Rated output power	26 kW / 27.5 kW / 30 kW
Max. apparent output power	26 kVA / 27.5 kVA / 30 kVA
Rated grid voltage	3/(N)/PE, 208 V / 220V / 240 V
Rated grid frequency	60 Hz
Rated grid output current	72.2 A
Max. output current	72.2 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
THDi	< 3%
Input AC (Grid side)	
Max. AC passthrough current	144.4 A
Rated input voltage	3/(N)/PE, 208 V / 220 V / 240 V
Rated input frequency	60 Hz
Input Generator	
Max. input power	26 kW / 27.5 kW / 30 kW
Max. input current	72.2 A
Rated input voltage	3/(N)/PE, 208 V / 220 V / 240 V
Rated input frequency	60 Hz
Output AC (Back-up)	
Rated output power	26 kW / 27.5 kW / 30 kW
Max. apparent output power	1.6 times of rated power with 2 s
Back-up switch time	< 10 ms
Rated output voltage	3/(N)/PE, 208 V / 220 V / 240 V
Rated frequency	60 Hz
Rated output current	72.2 A
Max. imbalance power per phase	33% rated power
THDv (@linear load)	< 2%
Efficiency	
Max. efficiency	97.9%
CEC efficiency	97.4%
CEC efficiency	99.9%
Protection	
Ground fault detection	Yes
Residual (leakage) current detection	Yes
Integrated AFCI	Yes
DC reverse-polarity protection	Yes
PV DC switch	Yes
Rapid shutdown NEC 2017	Integrated SunSpec-certified Transmitter
Compatible RSD receivers	See MLRSD Compatibility Sheet
Protection class / Over voltage category	I / II
General Data	
Dimensions (W × H × D)	22 × 41.3 × 13.64 in (560 × 1050 × 346.5 mm)
Weight	195.77 lbs (88.8 kg)
Topology	Transformerless
Self-consumption (night)	< 35 W
Operating ambient temperature range	-13°F to 140°F (-25°C to 60°C)
Relative humidity	0 - 100%
Ingress protection	TYPE 4X
Cooling concept	Intelligent fan-cooling
Max. operation altitude	8,202 ft (2500 m)
Compliance	UL1741SB, IEEE1547-2018, UL1699B, UL1998, FCCPart15ClassB, California Rule21, Hawaii Rule 14H, NEC 690.12-2020, CAN/CSA C22.2107.1-1
Features	
DC connection	Spring clamp terminals
Grid AC connection	Screw type terminal block
Back-up AC connection	Spring clamp terminals
Battery DC connection	Spring clamp terminals
Generator AC connection	Spring clamp terminals
Interface	7.0" LCD display & Bluetooth + APP
Monitoring platform	SolisCloud (modbus map and API sharing available upon request)
Revenue grade meter	Integrated ANSI C12.20 option
Communication	CAN, RS485-115200, Ethernet, Optional: Wi-Fi, Cellular, LAN

^① Supporting parallel 140A input.